



Logging Tools / Motorized Freepoint

1 7/16" Motorized Free Point Tool & CCL

Diameter
1 7/16 (3.65 cm)

Length
9.5' (2.9 m)

Housing Material
4140 Ht

Detector Type/s
Inductive

Line Voltages
70 mA operating current, 150 mA stall current
+/- 90 Vdc for upper arms
+/- 130 Vdc for lower arms

Connections
GO Pin & Box Standard
SIE Pin & Box Optional

Temperature Rating
350 Deg F (175 Deg C)

Pressure Rating
17,000 PSI

Telemetry Type
Variable Amplitude A.C.

Features
Stretch and torque function.
Ruggedized electronics, easily serviceable.
High temp high torque motor-exportable.
Easy to use portable panel or warrior compatible.

- A - Portable Freepoint Panel 500177
- B - Magnetic Casing Collar Locator..... 500173
- C - Upper Motor Section..... 500174
- D - Sensor Section..... 500175
- E - Lower Motor Section..... 500176

- 1 7/16" Motorized Anchor Section-Upper..... Temp Rating 350 Deg F
- 1 7/16" Motorized Anchor Section-Lower..... Temp Rating 350 Deg F
- 1 7/16" sensor Section Freepoint..... Temp Rating 350 Deg F
- 1 7/16" Magnetic CCL..... Temp Rating 350 Deg F

- Replacement Arms 2 3/8" to 3" Tubing (set 6)..... 500178
- Replacement Arms 3" to 5" Casing..... 500179
- Replacement Arms 5" to 7" Casing..... 500181

