



**Coupon Number:** \_\_\_\_\_ **Alloy Type:** \_\_\_\_\_  
Company Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Installation Depth: \_\_\_\_\_  
Chemicals in use: \_\_\_\_\_  
Date Installed: \_\_\_\_\_  
Date Removed: \_\_\_\_\_  
Comments: \_\_\_\_\_

---

**For Office use only:**

Initial Weight: \_\_\_\_\_ Final Weight: \_\_\_\_\_  
Weight Loss: \_\_\_\_\_  
Area Factor: \_\_\_\_\_  
MPY \_\_\_\_\_  
Type of Corrosion General: \_\_\_\_\_  
Localized: \_\_\_\_\_  
Comments: \_\_\_\_\_

---

**COUPONS MUST NOT BE PLACED BACK DOWN HOLE ONCE DEPLOYED.**

INSTRUCTIONS FOR REMOVAL OF COUPON HOLDERS FROM SUCKER ROD STRINGS

- 1) DO NOT remove any oil or down hole fluids from the rod once retrieved.
- 2) Coupons must be returned with the tool and not removed.
- 3) Place immediately in the tube provided as is.
- 4) Fill out paperwork – VERY IMPORTANT.
- 5) Place outside PVC tube and send back IMMEDIATELY.